

NUDURA 12" (305mm)  
STANDARD FORM UNIT

BRICK VENEER c/w  
1" (25mm) AIR  
SPACE AND BRICK  
TIES

WEEP HOLES AND  
THROUGH WALL  
FLASHING AS PER  
CODE OR AS  
SPECIFIED

1 1/2"  
(38mm) MIN.  
COVER

STEEL LINTEL WITH  
CONTINUOUS  
CAULKING AROUND  
FRAME TO MASONRY

BRICK VENEER  
BEYOND

ALUMINUM  
COMMERCIAL SIDE  
LIGHT FRAME

EXTERIOR  
CONCRETE  
SLAB

NUDURA 12"  
(305mm) BRICK  
LEDGE FORM  
UNIT BEYOND

COMPRESSIBLE  
FELT FILLER STRIP

1/2" (13mm)  
GYPSUM BOARD

HORIZ/VERT  
REINFORCEMENT AS PER  
CODE OR AS SPECIFIED

LINTEL  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED

VAPOR BARRIER  
SEALED TO CONCRETE

STEEL LINTEL AS  
SPECIFIED (w/NELSON  
STUDS OR BOLTS AS  
PER OPENING  
REQUIREMENTS)

FRAME ANCHOR CLIPS  
SECURED TO CONCRETE  
AND FRAME AS SPECIFIED

OPENING  
REINFORCEMENT AS  
PER CODE OR AS  
SPECIFIED



FLOOR FINISH  
AS SPECIFIED

CONCRETE  
SLAB ON GRADE

NUDURA 12"  
(305mm) DOUBLE  
TAPER TOP FORM  
UNIT OR HAND CUT  
TAPER AT WIDTH  
OF DOOR OPENING  
(BOTH SIDES)

The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.

### Non-Combustible Construction

 <p>Nudura Nudura Technical Support: 866-468-6299 International: +1 705-726-9499</p>	Detail: Nudura 12" (305mm) Form Unit, Concrete Mounted Aluminum Transom and Side Light at Head and Threshold, Brick Veneer Finish	File Name: E12E04	 <p>TREMCO Construction Products Group</p>
	Drawn by: TVC	Scale: 1 : 8	

tremcocpg.com