

NUDURA 12" (305mm)
STANDARD FORM UNIT

EXTERIOR FINISH AS
SPECIFIED

STEEL DOOR

1/2" (13mm) GYPSUM
BOARD

LINTEL
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

STEEL DOOR FRAME
c/w CAST IN
ANCHORS

THRESHOLD

EXTERIOR
CONCRETE SLAB

OPENING
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

FLOOR FINISH
AS SPECIFIED

NUDURA FORM
PANELS c/w INSERT
WEBS—CUT TO SUIT
CONCRETE CAP
PLACEMENT—ADDITIONAL
FORM SUPPORT AS
REQUIRED

CONCRETE
FLOOR SLAB
ON GRADE

COMPRESSIBLE
FELT FILLER
STRIP

EPS FOAM CUT DOWN
THICKNESS OF INTERIOR
SLAB AT EXTENT OF
DOOR OPENING WIDTH

HORIZ/VERT
REINFORCEMENT
AS PER CODE
OR AS SPECIFIED

The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.

Non-Combustible Construction

Detail: Nudura 12" (305mm) Form Unit, Steel Door at Head/Threshold, Concrete Cap at Threshold, Exterior Finish as Specified, Direct Attached

File Name:

E12H07

Drawn by: KS

Scale: 1 : 8

Date: 12/15/2021



Nudura Technical Support: 866-468-6299
International: +1 705-726-9499

tremcocpg.com



Construction Products Group