

NUDURA 8" (203mm)
STANDARD FORM UNIT

EXTERIOR FINISH AS
SPECIFIED

LINTEL REINFORCEMENT
AS PER CODE OR AS
SPECIFIED

ALUMINUM DRIP CAP
FLASHING INSTALLED BELOW
FINISH FOR FULL FRAME
WIDTH INSTALLED AS PER
CODE OR AS SPECIFIED

EXTENDED DOOR
FRAME SCREWED
DIRECTLY INTO
NUDURA CONCRETE
CORE

DOOR THRESHOLD

EXTERIOR CONCRETE
SLAB AND SLOPE AS
PER CODE

$\frac{3}{16}$ " (5mm) ACRYLIC
PARGE COAT

NUDURA 8" (203mm)
TAPER TOP FORM UNIT OR
HAND CUT TAPER BELOW
DOOR OPENING ONLY

NUDURA WATERPROOFING
MEMBRANE

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

VAPOR BARRIER
LAPPED AND SEALED
TO DOOR FRAME

$1\frac{1}{2}$ "
(38mm) MIN.
COVER

OPENING
REINFORCEMENT
AS PER CODE OR
AS SPECIFIED

BLOCKING BETWEEN
JOISTS

FLOOR FINISH
AS SPECIFIED

PROPRIETARY
EMBEDDED JOIST
ANCHORAGE SYSTEM
OR EQUIVALENT

FLOOR
JOISTS/TRUSSES
AS SPECIFIED

LAP VAPOR BARRIER
TO CONTACT DOOR
THRESHOLD

$\frac{1}{2}$ " (13mm)
GYPSUM BOARD

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.

Combustible Construction

Detail: Nudura 8" (203mm) Form Unit, Door Head/Threshold Detail,
Exterior Finish as Specified

File Name:

E8G08

Drawn by: KS

Scale: 1 : 8

Date: 12/8/2021

Nudura

Nudura Technical Support: 866-468-6299
International: +1 705-726-9499

tremcocpg.com

TREMCO

Construction Products Group