



NUDURA 8" (203mm)  
STANDARD FORM UNIT

BRICK VENEER c/w 1"  
(25mm) AIR SPACE AND  
BRICK TIES

HORIZ/VERT  
REINFORCEMENT AS PER  
CODE OR AS SPECIFIED

STEEL SUPPORT ANGLE c/w  
NELSON STUDS AS  
SPECIFIED

HAUNCHED SLAB  
REINFORCEMENT AS PER  
CODE OR AS SPECIFIED

THROUGH WALL  
FLASHING AS PER  
CODE OR AS  
SPECIFIED

NUDURA FLOOR  
TECHNOLOGY OR  
EQUIVALENT RIGID  
INSULATION AS SPECIFIED

3/16" (5mm) ACRYLIC  
PARGE COAT

INSTALL SLOPED INSULATION  
TO SUIT FROST PENETRATION  
DEPTH AS SPECIFIED BY  
LOCAL CODES

1/2" (13mm) GYPSUM  
BOARD

STEEL DOWELS TO MATCH  
VERTICAL REINFORCEMENT IN  
SLAB (EMBED 40x BAR  
DIAMETER) INSTALLED AS  
PER CODE OR AS SPECIFIED

FOAM FILL INTERLOCK GAPS  
CONTINUOUS WITH NUDURA  
LOW EXPANSION  
POLYURETHANE SPRAY FOAM  
BOTH INTERIOR AND  
EXTERIOR

SLAB ON GRADE

NUDURA FLOOR  
TECHNOLOGY

COMPACTED  
GRANULAR FILL

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER

*The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.*

**Below Grade Construction**

 Nudura Technical Support: 866-468-6299 International: +1 705-726-9499	Detail: Nudura 8" (203mm) Form Unit Haunched Slab Detail Brick Veneer Finish Insulated		File Name: B8D03	 Construction Products Group
	Drawn by: T.V	Scale: 1 : 8	Date: 11/30/2021	